



- ✓ Wind Vane for inductive sensors
- ✓ For relative wind direction
- ✓ System for offshore, arctic and other extreme conditions
- ✓ Customized output: NPN, PNP, Namur or fiber optic
- ✓ Heating units: 1 or 2 x 50 W, 24 VDC
- ✓ European patented no. 0813066

Product Description

The Wind Vane is made of brass, and is therefore very impervious to weather. It can be delivered with heating units, which ensure faultless function under extreme weather conditions. The Wind Vane can be configured to individual specifications.

The system is frictionless, which gives very high accuracy. It is possible to replace the heating units externally, without disassembling the Wind Vane.

Output Specifications

Sensor type	M8 standard inductive sensor, 10-40 VDC, PNP, NPN, NAMUR
No. of sensors	3 (possibility for security system)

Dimensions

Vane, length	237 mm
Wind Vane	193 mm + 50 mm (Sensor included)
Wind Vane	Ø60 (body)
Packaging	24 x 19 x 25 cm

Wind Vane

Brass Housing, Rotor of Stainless Steel

Type INV-00A

DWC

Materials

Body	Brass (CuZn39Pb3-MS1658-04)
Rotor	Stainless steel (AISI 316)
Ball bearing	Stainless steel (INA 626.2 Z VA)
Rotor/housing tightening	Patented labyrinth
Environment	Operating temperature -25 to 70°C (-13 to 158°F) Storage temperature -25 to 120°C (-13 to 248°F) Heating system > -25°C (> -13°F) Climatic protection Against high humidity, salt and dust
Mounting	Mounting hole M12 Fasten 30Nm
Weight	(without sensors and heating) Approx. 1340 g

Mode of Operation

The Wind Vane is usually placed approx. 10 m above ground level. It must be placed in a position where it is unimpeded by buildings and other wind-suppressing obstacles, so that turbulence at the instruments is reduced as much as possible. Wind Vane and adaptor must be mounted under observance of reliable craftsmanship and must be fastened in a way so that they present no danger to persons or goods, even at extreme blasts of wind. The pole and other devices forming part of the system must be effectively mutually connected to earthing systems for lightning protection and equipotential bonding.

Dimensions

